



## **RUGGED MLD-1 DISPLAY**

# Military-Grade LCD Display

The rugged **MLD-1** from Core Systems is a 1U rackmount LCD drawer designed for tactical and industrial applications where space efficiency and durability are critical. It features a 19" layflat clamshell display with a native resolution of 1280 × 1024 and supports both DVI and VGA inputs. A built-in Hulapoint pointing device and optional 4-or 8-port KVM enable streamlined control across multiple systems in a single rack.

Built in a rugged aluminum chassis with a 25-inch depth, the MLD-1 includes a reinforced quick-release cable retention arm and offers options for anti-reflective glass. Designed for demanding field use, it ensures dependable performance in mission-critical environments.

- Reinforced quick-release cable retention arm
- Tested to meet military standards
- Built in the USA

# **Featured Specifications**

### **Dimensions**

Height: 1.75" | Depth: 25.00" | Width: 19.00"

### Display

Clamshell 19" display

### Resolution

SXGA 1280 X 1024

### Display Input

RGB/DVI/HDMI/HD-SDI/S-Video Composite (Configurable)

#### Power

Power options available









# **Technical Specifications**

#### Dimensions

Height: 1.75 inches, Width: 19.00 inches, Depth: 25.00 inches Weight: 35.00 lbs

#### Display

Clamshell 19" display

#### Resolution

SXGA 1280 X 1024

#### **Display Input**

RGB/DVI/HDMI/HD-SDI/S-Video/Composite (Configurable)

#### **Power**

Power options available

#### **KVM Option**

4 or 8-port KVM for use with multiple computers in a single rack.

#### **Pointing Device**

Hulapoint pointing device

#### **Brightness**

400+ Nits

#### Color Depth

16.7M

#### Chassis

Lightweight aluminum chassis

# **Enviromental Specifications**

#### **Operational Temperature**

MIL-STD-810F, Method 501.5, Procedures I/II: -15°C to +55°C

### **Storage Temperature**

MIL-STD-810F, Method 501.5, Procedures I/II: -15°C to +55°C

### Humidity

MIL-STD-810F, Method 507.4: 95% RH, 48 hours at 40 - 65°C

#### Altitude

MIL-STD-810F, Method 500.4: 12,500 ft operation; 40,000 ft transport

#### Vibration

MIL-STD-810G, Method 514.6: 4.43 GRMS, 5-20000Hz, 60 min/axis

#### Shock

MIL-STD-810G, Method 516.6: 20g, 11ms functional; 40g, 11ms crash hazard

### **EMC**

MIL-STD-461F: CE & RE emissions

# Work With Core Systems Today

Core Systems designs and builds rugged servers, displays, mission computers, and integrated cabinet solutions for military and industrial applications. From our 85,000 sq. ft. San Diego facility, we deliver cutting-edge, durable computing solutions for mission-critical needs.

### Core Systems 13000 Danielson St Poway, CA 92064



